TECHNICAL SPECIFICATIONS

| | PARAMETERS | MEASUREMENTS |
|--------------------|---------------------------|---|
| BODY DIMENSIONS | Length | 2061 mm |
| | Width | 786 mm |
| | Height | 1113 mm |
| | Wheel base | 1347 mm |
| | Ground clearance | 177 mm |
| | Kerb weight | Single Disc: 139 kg Double Disc: 141 kg |
| | Seat length | 594 mm |
| | Seat height | 796 mm |
| | Fuel tank capacity | 12L |
| ENGINE | Туре | 4 Stroke, SI Engine |
| | Displacement | 162.71cc |
| | Max engine output | 9.9kW @7500 rpm |
| | Max torque | 14.58 N-m @5500 rpm |
| | Fuel system | PGM FI |
| | Bore x stroke | 57.300 x 63.096 |
| | Compression ratio | 10.0:1 |
| | Starting method | Self/Kick |
| TRANSMISSION | Clutch type | Multiplate Wet Clutch |
| | No. of gears | 5 |
| TYRES & BRAKES | Tyre size & type (front) | 80/100-17M/C 46P |
| | Tyre size & type (rear) | 130/70-17M/C 62P |
| | Brake type & size (front) | Disc-276 mm |
| | Brake type & size (rear) | Disc-220 mm, Drum-130 mm |
| FRAME & SUSPENSION | Frame type | Diamond |
| | Front suspension | Telescopic |
| | Rear suspension | Monoshack |
| ELECTRICALS | Battery | 12V, 4.0Ah |
| | Head lamp | LED LED |
| | | |

- +The technical specifications and design of the vehicle may vary according to the requirements and conditions without any notice.
 SP 160 meets Bharat Stage VI norms.
 Products shown in the picture may vary from the actual product available in the market.
 Accessories shown in the picture are not part of standard equipment.
 Conditions apply.



Honda Motorcycle and Scooter India Pvt. Ltd.

Registered Office: Plot No.1, Sector-03, IMT Manesar, Distt. Gurugram-122050 (Haryana)
Tel: +91(0)124-2290011, +91(0)6712800, Fax: +91(0)124-6712999

HONDA Visit us at: www.honda2wheelersindia.com Customer Care: customercare@honda2wheelersindia.com



















